

Product Specification [产品规格书]:	Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification	Date Issued	2021/06/30
	Date Revised	2023/12/26
	Version	A2

This specification is referred to the 2.54mm series wire to board connector

索引【INDEX】

1. 适用范围【Scope】
2. 规格与料号【Spec and Part number】
3. 材质与表面处理【Disposal of Material and surface】
4. 额定等级【Ratings and applicable wires】
5. 性能【Performance】
 - 5-1. 电气的性能【Electrical Performance.】
 - 5-2. 机械的性能【Mechanical Performance】
 - 5-3. 环境性能及其它【Environmental Performance and Others】
6. 综合插入力及拔出力【Insertion/Withdrawal Force】


Product Specification [产品规格书]:	Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification	Date Issued	2021/06/30
	Date Revised	2023/12/26
	Version	A2

【1.适用范围 Scope】

此种规格包括 2.54mm Pitch 2543 Series 连接器规格说明.

This Specification Covers the 2.54mm Pitch 2543 Series Connector Specification.

【2.规格与料号 Spec and Part number】

规格内容 Specification	产品料号 Production No.	产品图示 Picture of Product
端子/Terminal	2543TF-PSN1	
塑胶/Housing	2543HM-2*XX-N0HFBK	
针座/Wafer	2543WR-2*XX-LPSW1BX 2543WV-2*XX-LPSW1BX 2543WVS-2*XX-LPSW1BX	

【3.材质与表面处理 Disposal of Material and surface】

规格内容 Specification		材 质 Materials	表面处理 Disposal of Surface
端子/Terminal		磷铜/Phosphor Bronze	Nickel Plated: 50u" Min ,Bright Tin Plated: 100u" Min.
塑胶/Housing		PA66	UL 94V-0
针座/Wafer	Base	LCP	UL 94V-0
	PIN	黄铜/Brass	Nickel Plated: 50u" Min ,Matte Tin Plated: 100u" Min.

(上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification)


【4. 额定等级 Ratings and applicable wires】

项 目 【Item】	规 格 【Standard】	
额定电压 Rated Voltage (Max.)	250V	[AC/DC]
额定电流 Rated Current (Max.)	3A	
使用温度范围 Ambient temperature Range	-40℃~+125℃	
适用线径 Applicable wire insulation AWG(mm²)	AWG #20~22	Insulation O.D. 1.55mm(Max.)

【 *升温时含端子.Including terminal temperature rise. 】




Product Specification [产品规格书]:	Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification	Date Issued	2021/06/30
	Date Revised	2023/12/26
	Version	A2

【5.性能 PERFORMANCE】**5-1. 电气的性能 Electrical Performance.**


项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-1-1	接触阻抗 Contact Resistance	公母配合,开放电压 20mV 以下,电流 10mA 检测连接器 A~B 区. Mate connectors, measure by dry circuit, 20mV MAX, 10mA. (Based upon EIA-364-06A). 	Initial: 20 milliohms Max. After Test: 40 milliohms Max.
5-1-2	绝缘阻抗 Insulation Resistance	公母配合,在相邻端子,端子与地片之间,使用 500V 的直流电,检测连接器. Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond.B)	1000 Megohms Min.
5-1-3	耐电压 Dielectric Strength	公母配合,在相邻端子,端子与地片之间,使用 1000V 的交流电 1 分锺,检测连接器. Mate connectors, apply 1000V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)	外观无损伤, 无打火花 No Breakdown and Flashover
5-1-4	铆线后端子接触 阻抗 Contact resistance on crimped portion	铆线后之端子,开放电压 20mV 以下,电流 10mA 检测连接器. Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA.	10 milliohms Max.

Product Specification [产品规格书]:	Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification	Date Issued	2021/06/30
	Date Revised	2023/12/26
	Version	A2

5-2. 机械的性能 Mechanical Performance.


项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-2-1	插拔力 Insertion & Retention Force	以每分钟 25.4±3mm 的速率插入和拔出. Insert and withdraw Connectors at the speed rate of 25.4 ±3mm/minute.	参照第 6 项 Refer to paragraph 6
			
5-2-2	端子保持力 Terminal/ Housing Retention Force	以每分 25.4±3mm 的速率,将端子从 Housing 内轴向拔出的力量. Apply axial pull out force at the speed rate of 25.4±3mm/minute on the terminal assembled in the housing.	19.6N {2.0kgf} Min.
			
5-2-3	端子插入力 Terminal Insertion Force	铆线后之端子插入 Housing 所需最大力量. Insert the crimped terminal into the housing.	9.8N {1.0kgf} Max.
5-2-4	Pin 针保持力 Pin Retention Force	以每分 25.4±3mm 的速率,将 PIN 针从 Wafer 内轴向拔出的力量. Apply axial push force at the speed rate of 25.4 ±3mm/minute.	14.7N {1.5kgf} min.
			

Product Specification [产品规格书]:	Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification	Date Issued	2021/06/30
	Date Revised	2023/12/26
	Version	A2

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】		
5-2-5	端子压着强度 Tensile strength (Crimped connections)	固定铆线后的端子, 使电线与端子分离时所需的最小力量.	AWG#	#20	#22
		Fix the crimped terminal, apply axial pull out force on the wire. (Do not crimp insulation part).	Spec. .kgf. Min.	5.0	4.0
			Note> As for unspecified wire sizes in this specification define values with clients		

5-3. 环境性能及其它 Environmental Performance and Others.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-1	重复插拔 Repeated Insertion/ Withdrawal	以每分钟不超过 10 次的速率,将公母插拔 30 次. When mated up to 30 cycles repeatedly by the rate of 10 cycles per minute.	接触阻抗 Contact Resistance	40 milliohms Max.
5-3-2	温升测试 Temperature Rise	公母连接器配合后, 加载额定电流直到温度上升到稳定状态, 然后再测量温升 (EIA364-70,Method 1) Mating connectors shall be energized at rating current until thermal stability is achieved, and then measured the temperature rise. (EIA364-70,Method 1)	温升测试 Temperature rise	30°C Max.

Product Specification [产品规格书]:			Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification			Date Issued	2021/06/30
			Date Revised	2023/12/26
			Version	A2
5-3-3	震动/机械冲击 Vibration/Mechanical Shock	冲击: 1.加速度 35g、脉宽 5~10ms、半正弦 2.每轴 10/次、6 个轴向 振动: 三个相互垂直的轴中各进行 8 小时振动测试, 使用 5-1000HZ 1.81grms 没有任何端子对的电阻在 1 微秒内超过 7.0Ω的情况发生 Shock : 1. Acceleration 35 g, Duration 5~10 ms,Half Sine Wave 2.Each axis 10/times ,6 axes. Vibration :8 hours of vibration test in each of the three vertical axes, using 5-1000 HZ 1.81grms Does not occur when the resistance of any terminal pair exceeds 7.0Ω within 1 microsecond.	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
			瞬断 Discontinuity	1 micro-second Max.

Product Specification [产品规格书]:	Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification	Date Issued	2021/06/30
	Date Revised	2023/12/26
	Version	A2

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-4	耐热性 Heat Resistance	125±2°C,96 hours. (Based upon MIL-STD-202 Method 108A Cond.A)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-5	耐寒性 Cold Resistance	-40±5°C,96 hours. (Based upon EIA-364-105)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-6	耐湿性 Humidity	温度: 40±2°C 湿度: 90~95%(RH) 持续时间: 96 hours Temperature: 40±2°C Relative Humidity: 90~95% Duration: 96 hours (Based upon EIA-364-31A/MIL-STD-202 Method 103B Cond.B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
			耐电压 Dielectric Strength	Must meet 5-1-3
			绝缘阻抗 Insulation Resistance	500 Megohms Min.
5-3-7	温度变化 Temperature Cycling	从-40°C持续30分锺升至+125°C持续30分锺,循环5次. 5 cycles of: a) -40°C 30 minutes. b) +125°C 30 minutes. (Based upon EIA-364-32B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-8	盐水喷雾 Salt Spray	在温度 35±2°C,盐水浓度 5±1%下,盐水喷雾 48±1小时. 48±1 hours exposure to a salt spray from the 5±1% solution at 35±2°C. (Based upon EIA-364-26B/MIL-STD-202 Method 101D Cond.B).	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.

Product Specification [产品规格书]:			Document No	PS-2543-01
Subject [主题]: 2.54mm Pitch 2543 Series Connector Specification			Date Issued	2021/06/30
			Date Revised	2023/12/26
			Version	A2
5-3-9	焊锡附着性 Solder-ability	焊接时间: 3~5 秒. 焊接温度: 245±5℃. Soldering Time: 3~5second. Solder Temperature: 245±5℃. (Based upon EIA-364-52)	Solder Wetting	浸渍面积需 95%以上 95% of immersed area must show no voids, pin holes.
5-3-10	焊锡耐热性 Solder-Resistance	焊接时间: 5~10 秒. 焊接温度: 255+5/-5℃. Soldering time:5~10 sec solder. Temperature:255+5/-5℃. (Based upon EIA-364-56A)	外观 Appearance	无异状 No Damage

【6.综合插入力及拔出力 INSERTION/WITHDRAWAL FORCE】 <Connector mating force>

PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	30 次拔出力(最小值) 30 th Withdrawal (kgf Min.)	PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	30 次拔出力(最小值) 30 th Withdrawal (kgf Min.)
2*02	3.2	1.00	2*09	14.4	4.50
2*03	4.8	1.50	2*10	16.0	5.00
2*04	6.4	2.00	2*11	17.6	5.50
2*05	8.0	2.50	2*12	19.2	6.00
2*06	9.6	3.00	2*13	20.8	6.50
2*07	11.2	3.50	2*14	22.4	7.00
2*08	12.8	4.00	/	/	/

注：以上插拔次数为 30 次

Note：Insertion and Withdrawal for 30Cycles